



OPERATOR INTERFACE PRODUCTS APPLICATION NOTE

Subject: Installing SVGA Drivers for the AT5+ in Windows NT 4.0

AN# 1053A

Date: 11/01/96

Name: Irvin Hayes Jr.

Page: 1 of 1

Description: Installation Instruction for the SVGA Drivers in Windows NT 4.0

The following is instruction on installing the SVGA Drivers in Windows NT 4.0:

1. From the Start Menu selecting Settings | Control Panel.
2. Double Click the Display Icon and the Display Properties window will appear.
3. Select the Settings Tab.
4. Select the Display type button and the Display Type Menu will appear.
5. Select the Change button and click on the Chips & Technologies in the Manufacturers list. You will the see Chips & Technologies Accelerators (64300 64310 65545 65548 65550). Select the OK button.
6. When you are asked to install third party drivers, select yes to proceed.
7. Follow the onscreen instructions for selecting the driver to install the drivers from.
8. After Windows NT has copied all the drivers a window will appear and say that all the drivers were successfully installed. Select the OK button.
9. Close the Display Type and Display properties windows. Select Yes to restart Windows NT.
10. When the system reboot select the VGA Mode from the boot menu.
11. When the system has completed its boot sequence into Windows you will see a window titled "Invalid Display Settings", select the OK button.
12. Make sure that the properties are set to 256 color on the Color Palette, 640x480 on the Desktop Area and 60 hertz on the Refresh Frequency.
13. Select the Test button and what the screen to make sure the bitmap is displayed properly. Select Yes if it is.
14. Select the OK button in the Display Properties window and restart the computer.
15. You may now reboot with the default boot menu selection and it will boot in SVGA mode.