Modernize

Easy migration to the latest HMI with high-resolution on wide-display



304050 60

Basic HMI ST6000 Series powered by GP-Pro EX



Agitatetime

sulet

00,00

profaceamerica.com

Mixer

nor Message

0

RUT

Achieve a high level of visualization with the new Basic HMI

Refine			Simple & Easy		Connected & Secure	
Achieve the previously unimaginable and bring displays to life with high resolution and 16 million colors.			Use the same application (GP-Pro EX) and leverage existing assets.		User-friendly protocols allowing you to connect your devices with ease via multiple interfaces and connect OT to IT.	
			GP4000 W model (4:3, Wide)	Same application	EZ Series * Pro-face Remê te HIMI * Oreface Remê te	
	pecificatio		EX			
Μ	odel No	PFXST6700WADE	PFXST6600WADE	PFXST6500WADE	PFXST6400WADE	PFXST6200WADE
Display	Size/ Resolution	15.6"W (1,366 x 768)	12.1"W (1,280 x 800)	10.1"W (1,024 x 600)	7"W (800 x 480)	4.3"W (480 x 272)
	Color	16M colors				
	Touch	Analog				
Interface	Serial	RS-232C x1, RS-422 / 485 x1			RS-232C / 422 / 485 x1 *1	
	Ethernet	10BASE-T / 100BASE-TX x2				10BASE-T / 100BASE-TX x1
	USB	Type-A x1, Micro-B x1				
	SD card	-				
F	Front frame	Aluminum				
Certification		IP65F, Type 1, Type 4X (indoor use only), Type 13 (on the front panel when properly installed in an enclosure), CE, UL and cUL, RMC, KC, EAC, RoHS, WEEE				
Installation		Tooling free fastener				Fastener
N	lemory	Application memory: Media : FLASH EPROM / Screen area: 64MB / User font area 8 MB / Logic program area: 132KB Backup memory: Screen Area: SRAM 320KB, Variable Area: SRAM 64KB Battery: Replaceable battery / Primary battery for clock data backup				
Protocol		Connect to up to 2 drivers at the same time				
				*1 COM port supports		



The new software is also available; BLUE offers an alternative experience in HMI project design.

Visit the ST6000 web site for more information

profaceamerica.com/en-US/content/st6000-series

Contact Us (Worldwide Pro-face)

https://profaceamerica.com/en-US/content/contact-pro-face-america

©2020 Schneider Electric Japan Holdings Ltd. All Rights Reserved.