

ST-6200WA Basic HMI



Features:

- Aluminum Front Panel
- 16 Million Colors
- Enhanced Cybersecurity
- Easy to Install, No Tools Needed
- Single Touch Analog Display
- Ethernet Port, Serial (COM 1)

Performance Specifications

Part Numbers	PFXST6200WAD (BLUE)	PFXST6200WADE (GP-Pro EX)
Graphics Display Resolution	WQVGA TFT (480 x 272 Pixels)	
Display Type and Size	TFT Color LCD (4.3-inch) Wide	
Display Colors	16 million colors	
Touch Panel	Resistive film (analog, single touch)	
Effective Display Area	95.04 x 53.86 mm (3.74 x 2.12 in)	
Touch Panel Resolution	1024 x 1024	
Backlight	Backlight White LED (Not user replaceable. When replacement is required, contact customer support.)	
Backlight Service Life	50,000 hours or more (continuous operation at 25 °C [77 °F] before backlight brightness decreases to 25%)	
Brightness Control	16 levels (Adjusted with touch panel or software)	
Interface	USB (Type A)	Connector: USB 2.0 (Type A) x 1, Power supply voltage: 5 Vdc ±5 %, Maximum current supplied: 500 mA, Communication distance: 5 m [16.4 ft.]
	USB (Type - microB)	Conforms to USB 2.0 (micro-B) x 1, Maximum transmission distance : 5 m [16.4 ft]
	Ethernet	IEEE802.3i/IEEE802.3u, 10BASE-T/100BASE-TX, Connector: Modular jack (RJ-45) x 1
	Serial(COM1)	Asynchronous Transmission: RS-232C/422/485, Data Length: 7 or 8 bits, Stop Bit: 1 or 2 bits, Parity: None, Even or Odd, Data Transmission Speed: 2,400 to 115,200 bps, Connector: D-Sub 9 (plug)


General Specifications

Part Numbers	PFXST6200WAD (BLUE)	PFXST6200WADE (GP-Pro EX)
Input Voltage	Rated Input Voltage: 24 Vdc / Input Voltage Limits: 19.2 to 28.8 Vdc	
Power Consumption	3.6 W or less when power is not supplied to devices via from USB, 2.8 W or less when screen turns off the backlight (standby mode) (Max 6.9 W)	
In-Rush Current	30 A or less	
Storage Temperature	-20 to 60 °C (-4 to 140 °F)	
Shock Resistance	IEC/EN 61131-2 compliant 147 m/s ² , X, Y, Z directions for 3 times	
Certifications	UL 61010-2-201 and CSA C22.2 No61010-2-201, KC KN1, KN61000-6-2, RCM EN61000-6-4, CE EN 61131-2, EN61000-6-4, EN61000-6-2, RoHS, REACH Regulation EC 1907/2006, WEEE Directive 2012/19/EU	
Operating Temperature	0 to 50 °C (32 to 122 °F)	
Voltage Drop	2 ms or less	
Corrosive Gas	Free of corrosive gases	
Pollution Degree	For use in pollution degree 2 environment	
Cooling method	Natural air circulation	
Dust	0.1 mg/m ³ (10 ⁻⁷ oz/ft ³) or less (non-conductive levels)	
Voltage Endurance	1,000 Vac, 20 mA for 1 minute (between charging and FG terminals)	
Vibration Resistance	IEC/EN 61131-2 compliant, 5 to 9 Hz single amplitude 3.5 mm [0.14 in.], 9 to 150 Hz fixed acceleration: 9.8 m/s ² , X, Y, Z directions for 10 cycles (approx. 100 min.)	
Insulation Resistance	500 Vdc, 10 MΩ or more	
Structure	IP65F, Type 1, Type 4X (indoor use only), Type 13 (on the front panel when properly installed in an enclosure) ^{*1}	
Weight	0.4 kg (0.88 lb) or less	
External Dimensions	134.5 x 108.5 x 43 mm (5.3 x 4.27 x 1.69 in)	
Panel Cut-Out Dimensions	118.5 x 92.5 mm (4.67 x 3.94 in) ^{*1} Panel thickness area: 1.6...5 mm (0.06...0.2 in) ^{*2}	
Warranty	Two (2) years	

¹ For dimensional tolerance, everything +1/-0 mm (+0.04/-0 in) and R in angle are below R3 (R0.12 in)


² Even if the installation wall thickness is within the recommended range for the "Panel Cut Dimensions", depending on wall's material, size, and installation location of this product and other

External Dimensions



- 1 Front
- 2 Left
- 3 Bottom

Panel Cut-Out Dimensions



Panel Cut Out	A	B	C
4.3" Wide	118.5 ±0.7 mm (4.67 ±0.03 in.)	92.5 ±0.4 mm (3.64 ±0.02 in.)	1.6 to 5 mm (0.06 to 0.2 in.)

Ordering Information

Model Number	Description
PFXST6200WAD	4.3"W Basic HMI 480 x 272 Pixels 16M colors display with analog signal touch panel, Ethernet(RJ45) x 2, USB Host, 24VDC, Serial Port (COM 1), programmable with BLUE.
PFXST6200WADE	4.3"W Basic HMI 480 x 272 Pixels 16M colors display with analog signal touch panel, Ethernet(RJ45) x 2, USB Host, 24VDC, Serial Port (COM 1), , programmable with GP-Pro EX.

Options

Part Number	Description
ZC9AF31	Installation fastener (2 pieces/set).
PFXZCIWG43	Installation Gasket
CA5-DCNM-01	Connector to connect DC power supply cables.
PFXZCIDS42	Disposable, dirt-resistant sheet for the display (5 sheets/set) for STW-64200WA.
FP-US00	Connects a USB device.
CA5-USBEXT-01	Extension cable that attaches USB interface to front panel.
PFXZCBCLUSA1	Clamp to prevent disconnection of USB cable (USB Type A, 1 port, 5 clamps/set)

Pro-face America
 Phone: 734.477.0600
 www.profaceamerica.com

Customer Service Hotline: 800.289.9266

For more information

ACCESS www.profaceamerica.com